

| Bmod in [gauss] for 32mm 35T #606D | | axial=vertical distance from center (0.75m=platform top) | | | | | | | | | |
|---------------------------------------|------|--|---------|--------|--------|--------|--------|--------|-------|-------|-------|
| | | 0.75 | 1.00 | 1.25 | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 |
| radial distance R in [m] | 0.00 | 3129.38 | 1340.16 | 690.16 | 400.52 | 252.62 | 169.40 | 119.05 | 86.83 | 65.26 | 50.28 |
| | 0.25 | 2598.53 | 1200.10 | 642.01 | 380.68 | 243.30 | 164.58 | 116.36 | 85.23 | 64.26 | 49.63 |
| | 0.50 | 1621.38 | 891.88 | 524.98 | 329.48 | 218.33 | 151.31 | 108.81 | 80.70 | 61.41 | 47.77 |
| | 0.75 | 901.61 | 593.71 | 391.91 | 265.05 | 184.73 | 132.62 | 97.83 | 73.93 | 57.08 | 44.89 |
| | 1.00 | 502.94 | 380.02 | 278.46 | 203.21 | 149.69 | 111.93 | 85.13 | 65.85 | 51.77 | 41.30 |
| | 1.25 | 294.50 | 244.33 | 194.53 | 151.89 | 117.99 | 91.97 | 72.25 | 57.34 | 46.00 | 37.31 |
| | 1.50 | 182.60 | 161.04 | 136.38 | 112.57 | 91.67 | 74.29 | 60.25 | 49.07 | 40.21 | 33.19 |
| | 1.75 | 119.40 | 109.56 | 97.02 | 83.65 | 70.88 | 59.47 | 49.69 | 41.50 | 34.73 | 29.18 |
| | 2.00 | 81.73 | 76.97 | 70.37 | 62.75 | 54.93 | 47.49 | 40.74 | 34.83 | 29.74 | 25.42 |
| | 2.25 | 58.15 | 55.72 | 52.12 | 47.68 | 42.84 | 37.98 | 33.35 | 29.11 | 25.33 | 22.02 |
| | 2.50 | 42.73 | 41.43 | 39.39 | 36.75 | 33.72 | 30.52 | 27.34 | 24.31 | 21.52 | 18.99 |
| | 2.75 | 32.27 | 31.54 | 30.35 | 28.74 | 26.80 | 24.68 | 22.49 | 20.33 | 18.27 | 16.35 |
| | 3.00 | 24.95 | 24.52 | 23.80 | 22.79 | 21.54 | 20.11 | 18.59 | 17.04 | 15.52 | 14.07 |

